

# UNIT HEATERS

20 C dT	REFERENCE	UH1-UH2	UH3-UH7	Door Curtain 1	Door Curtain 2
<b>DESIGN INFORMATION</b>	No off	2	5	1	1
	Heating Flow Temp	75 degC	75 degC	75 degC	75 degC
	Heating Return Temp	55 degC	55 degC	55 degC	55 degC
	Room Temperature (deg C)	16 degC	18 degC	15 degC	20 degC
	Output (kW)	8,783 W	15,939 W	14,000 W	12,320 W
	Water Flow Rate (l/s)	0.105 l/s	0.191 l/s	0.167 l/s	0.147 l/s
	Height	650 mm	800 mm	254 mm	254 mm
	Width	650 mm	800 mm	1,621 mm	1,113 mm
	Depth	315 mm	315 mm	265 mm	265 mm
	Colour	White RAL 9010	White RAL 9010	White RAL 9010	White RAL 9010
	Connections (mm)	20 mm	25 mm	20 mm	20 mm
	Weight	42 kg	62 kg	25 kg	20 kg
	MV & BMS Control	Yes	Yes	Yes	Yes
	Comments				
<b>INSTALLATION DATA</b>	Manufacturers Name	Dunham Bush	Dunham Bush	Dunham Bush	Dunham Bush
	Model /Type	Series UH Size 3	Series UH Size 4	Sentinal Model 270 W15	Sentinal Model 270 W10
	Installation Date	2014	2014	2014	2014
	Life Expectancy (yrs)	20 years	20 years	20 years	20 years
<b>LOCATION</b>	Building Name	Example Name	Example Name	Example Name	Example Name
	Building Reference	Example Reference	Example Reference	Example Reference	Example Reference Offices
	Room	Example Room	Example Room	Example Room	Example Room
	Floor	Level 1	Level 1	Level 1	Level 3
	Grid Re (x-y coord)				
<b>ELECTRICAL</b>	Electrical Supply	240 1Ph	240 1Ph	240 1Ph	240 1Ph
	Power (kW)	0.2 kW	0.2 kW	0.2 kW	0.2 kW
	FLC (amps)	4.0 amps	4.0 amps	4.0 amps	
	Starting Method	DOL	DOL	DOL	DOL