JOHN CULLEN

LIGHTING FOR HOUSE AND GARDEN



Product notes

45° angle of adjustment. Suitable for accenting plants, walls and decorative features. Complete with 13amp plug.

Voltage input	230v
Wattage maximum	20w
Lamp cap	GU5,3
Source type	Tungsten Halogen
Product type	Class II
IP rating	IP20

Lamp options

12v 50mm Dichroic GU5,3 20w max Tungsten Halogen 12v 50mm Dichroic GU5,3 20w max Tungsten Halogen IRC energy saver 12v 48mm Halospot GY4 20w Tungsten Halogen 12v 50mm LED GU5,3 4-10w LED

Installation notes

- 1 Connection Feed mains voltage cable to required location.
- 2 Lenses Sandblasted lenses lift and diffuse the light, giving a full wash effect. Softening lenses soften the edge of the scallop, maintaining some definition. These are added where appropriate.
- 3 Lamps With a John Cullen Design the lamp beam angles and lens specification are provided on the drawings and should be installed as shown.
- 4 Temperature Light fitting becomes hot to the touch in operation and should not come into contact with fabrics, furniture or soft furnishings. Fittings used at low level become hot to the touch and consideration must be given to a child touching them or objects left on them when off, and not removed before switching back on.
- 5 5 amp circuit Electrician to remove 13 amp plug supplied and replace with a 5 amp plug where required.

PLEASE NOTE:-These notes are for guidance only. John Cullen accepts no responsibility for any installation using the above notes and the final decision on installation remains with the installer.

Product codes

85

G341001	White
G341006	Bronze
G341010	Silver grey
G341012	Gun metal

80

Accessories

SG50	Sandblasted glass to provide an even
	wash without scallop.
HC50	Honeycomb louvre for extra low glare.

- SL50 Lens for softening the scallop edge.
- LL50 Spreader lens to elongate the beam width.
- UV50 Ultra violet lens to limit UV.

Coloured glass lenses available on request.



0905140911©