





Price offer and specifications of ECO - 800 water purifier and ionizer.

Specifications/Models	ECO-800
Output capacity	Total output ~ 720 LPH of alkaline ionized water and ~80 LPH of acidic water (ratio between alkaline and acidic water can be regulated).
Size of the cabinet	800 x 600 x 300 Wall mountable
Cabinet material	Polycarbonate
Inlet and outlets	Mains water inlet - 1/2" Alkaline ionized water outlet - 1/2" Acidic water outlet -1/4" Flushing acid inlet - 1/4" Flushing acid outlet - 1/4"
Power supply	220VAC
Power consumption	Average 500 W/H depending on the source water
Flow meter	+
Input valve	+
Temperature switchers on the cell	+
Acid pump for cell flushing	+
Durability	Able to stand up to adverse conditions such as dust and high humidity
Type of cell	R-400 
Life expectancy of electrodes and membrane	~ 10 years
Fittings	LLDPE tubing + Kynar.

<p style="text-align: center;">Accessories</p>	<p>Alkaline water tubing ~ 3 m. Acidic water tubing ~ 3 m. Mains water tubing ~ 3 m. Acid tubing ~ 3 m. Mains water fitting – 1 pcs. Wall mounting lugs -1 set</p>
<p style="text-align: center;">PLC</p>	<p style="text-align: center;">Unitronics/Jazz</p> 
<p style="text-align: center;">Price EXW Envirolyte factory</p>	<p style="text-align: center;">€ 6 450,00</p>
<p style="text-align: center;">Warranty</p>	<p style="text-align: center;">Two years</p>
<p style="text-align: center;">Delivery</p>	<p style="text-align: center;">Upon order confirmation</p>

The offer is valid till 31.03.2014

Envirolyte Industries International Ltd.
Tallinn, Estonia
January, 2013